

# Self-Propelled Articulating Boom

of motion, enhanced
with Genie's new
innovative lift
structure, increases
operator productivity



## **Standard Features**

- 26.4 m (86 ft) working height
- 18.3 m (60 ft) outreach
- 8.8 m (29 ft ) up and over clearance
- 1.83 m (6 ft) jib boom witn 128° range of motion
- 2.44 m (8 ft) steel platform
- 227 kg (500 lb) lift capacity
- Oscillating front axle
- Dual fuel (Petrol/LPG) or diesel engine options
- Fully proportional platform controls with ramp up/down feature
- Hydraulic platform rotation
- 360° continuous turntable rotation
  12V DC auxiliary power unit
- Full time positive traction drive
- Full time 4WD (on 4WD models)
- Closed-loop hydrostatic drive 4 Wheel Steer &
- Hydraulic Oil Cooler
- Drive enable system
- Self-leveling platform
- Onboard full diagnostics
- Anti-restart engine protection
- Auto engine fault shutdown
- Engine monitoring display
- AC wiring to platform
- High-angle steer
- Extra Wide RT foam-filled tyres
- Wire braided hydraulic hoses
- Tilt alarm
- Horn
- Hour meter

# **Options** and **Accessories**


- Two or four-wheel drive models

  Two or four-wheel
- steer options
  liquid cooled or air
- cooled diesel engines

  Alarm package
- Cold start packages
- Onboard welder packages
- 3500 watt AC generator
- Air line to platform
  Weld cables to platform
- Hostile environment packages
- Platform work lights
- Platform swing gate

# Range of Motion


Oscillating axle




- Platform rail pinch guard
- Control box covers
- Driving lights
- . LPG tank
- Second LPG tank with carrier
- Tool tray

# **Standards Compliance**

■ CE EN280





110

# **Specifications**

|   |                                   | Metric   | US          |
|---|-----------------------------------|--|-------------|
|   | Working height max*               | 26.4 m   | 86 ft       |
|   | Platform height max               | 24.4 m   | 80 ft       |
|   | Height - stowed                   | 3 m  | 9 ft 10 in  |
|   | Length - stowed                   | 11.27 m  | 37 ft       |
|   | Length - transport                | 9.14 m   | 30 ft       |
|   | Width                             | 2.49 m   | 8 ft 2 in   |
|   | Wheelbase                         | 2.74 m   | 9 ft        |
|   | Ground clearance                  | 30 cm  | 12 in       |
|   | Platform langth                   | 91 cm  | 36 in       |
|   | Platform width                    | 2.44 m   | 96 in       |
|   |                                   | 18.3 m   | 60 ft       |
|   | Un and over clearance             | 8.83 m   | 29 ft       |
| 1 | Lift capacity                     | 227 kg   | 500 lb      |
|   | Turning radius - 4WS inside       | 2.1 m  | 7 ft        |
|   | 4WS outside                       | 4.6 m  | 15 ft       |
|   | 2WS inside                        | 4.4 m  | 14 ft 6 in  |
|   | 2WS outside                       | 7.5 m  | 24 ft 6 in  |
|   | Turntable rotation                | 360° continuous  |             |
|   | Tailswing                         | 91.4 cm  | 3 ft        |
|   | Power source                      | Deutz Diesel F4L 913 57 kw (77 hp) air cooled<br>Perkins Diesel 704-30 47 kw (63 hp) liquid cooled<br>GM 3.0L Petrol/LPG 60 kw (80 hp) |             |
|   | Drive speed - stowed              | 4.82 km/h  | 3.0 mph     |
|   | Drive speed - raised <sup>1</sup> | 1 km/h   | 0.6 mph     |
|   | Controls                          | 12V DC proportional  |             |
|   | Platform rotation                 | 160°   | 160°        |
|   | Auxiliary power unit              | 12V DC   |             |
|   | Tyres - foam filled               | 18x19.5  |             |
|   | Gradeability <sup>2</sup> - 2WS   | 30%  | 30%         |
|   | - 4WS                             | 50%  | 50%         |
|   | Hydraulic tank capacity           | 170 litre  | 45 gal      |
|   | Fuel tank capacity                | 125 litre  | 33 gal      |
|   | Weight** - 2WS                    | 16,284 kg  | 35,900 lbs. |
|   | - 4WS                             | 17,010 kg  | 37,500 lbs. |
|   |                                   |  |             |

- <sup>1</sup> In lift mode (platform raised), the machine is designed for operation on firm level surfaces only.
- 2 Stowed position only
- \*The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
- \*\*Weight will vary depending on options and/or country standards.

Distributed By:

# Genie Industries

GENIE UNITED KINGDOM

GENIE UNITED STATES
18340 NE 76th Street
P. O. Box 97030
Redmond, Washington 98073-9730
Telephone +1 (425) 881-3800
Fax +1 (425) 883-38475
http://www.genieindustries.com