

Rough Terrain
Self-Propelled
Scissor Lift

The ultimate scissor
lift for narrow, rough
terrain applications.



Genie Industries

GS-3384 RT

- Large platform with durable diamond-plate aluminium flooring. A single 1.52m (60in) multi-position slideout extension deck, on the front of the machine, comes standard. A second 1.22 m (48 in) slide-out extension deck, on the rear of the machine, is available as an option. The super deck also available as an option, has longer front and rear extension decks to give an extended length of 7.30m
- · Slide-out engine tray allows easy access to components.
- Optional automatic leveling hydraulic outriggers

Standard Features

- 12.1 m (39 ft) working height
- 1,134 kg (2,500 lb) platform capacity
- Front platform extension decks
- · Positive traction-control
- 50% gradeability
- · Proportional drive
- · Powered by Deutz Diesel engine (standard) or GM petrol/LPG engine (optional)
- · Slide-out engine tray for easy maintenance
- · Foam-filled tyres
- AC wiring to platform
- Descent alarm
- Tilt sensor with an audible alarm
- Horn
- · Hour meter

Options and Accessories

- Automatic levelling hydraulic outriggers
- · Rear extension deck
- Super deck (7.30m extended)
- Hydraulic oil cooler
- · High floatation tyre package
- 3,500 watt generator (230 Volt/50hz)

Standards Compliance

■ CE EN280

6	1
T	
A	
<u>***</u>	
C	
Specifications	
Model	GS-3384 RT

opounioaciono			
Model	GS-3384 RT		
	Metric	us	
Working height*	12.1 m	39 ft	
Platform height	10.1 m	33 ft	
(A) Height - stowed			
guardrails	2.68 m	105.5 in	
guardrails lowered	2 m	78.75 in	
(B) Height - stowed (platform)	1.55 m	61 in	
© Length			
stowed	3. 94m	155.25 in	
stowed-w/outriggers	4.88 m	192 in	
single deck extension	5.40m	212.5in	
w/dual deck extension	6.57m	258.5in	
(D) Width-standard tyres	2.13 m	84 in	
(E) Wheelbase	2.88 m	113.5 in	
F Ground clearance	33 cm	13 in	
Platform width	1.83 m	72 in	
H) Platform length			
single deck extended	5.4m	212.5in	
dual deck extended	6.57m	258.5in	
Lift capacity	1,134 kg	2,500 lb	
Extension deck capacity (max)	227 kg	500 lb	
Turning radius - outside	5.94 m	234 in	
Turning radius - inside	3.09 m	121.5 in	
Power source cooled	Deutz Diesel F3L 1011 27 kw (36 hp), air		
000100	GM 1.6L 39kw (52hp) water cooled of		
Auxiliary power unit	12 volt DC		
Drive speed - stowed	6.4 km/h	4 mph	
Drive speed - raised	1.1 km/h	0.7 mph	
Raise/lower speed	45/29 sec	on as any condition of the	
Tyres - rough terrain	25.4 cm x 41.9 cm	10 in. x 16.5 in	
	Control of the contro		

5,452 kg * The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height. ** Weight will vary depending on options and/or country standards.

75.7 litre 75.7 litre

50%

Unit Weight Modifiers for Options

Outriggers Dual extension decks

Gradeability (4x4)

Fuel tank capacity

Weight*3

Hydraulic tank capacity

add 748kg add 136kg add 1,650lb

50%

20 gal

20 gal

12,020 lb

Distributed By

Genie Industries

O GENIE UNITED KINGDOM

The Maltings, Grantham Lincolnshire NG31 6BH England Telephone: +44 (0)1476 584333 Fax: +44 (0)1476 584334 http://www.genielift.com O GENIE UNITED STATES

18340 NE 76th Street P.O. Box 97030 Redmond, Washington 98073-97 Telephone +1 (425) 881 1800 Fax +1 (425) 883 3475 http://www.genielift.com

For further information, please contact your local distributor or the Genie sales office listed. Continuous improvem drawings in this brochure are for illustrative purposes only. Refer to the appropriate Genie GS-3384 RT Operator's Mei 3384 RT, or betwiese cit responsibly, may result in serious injury or death. Copyright © 2001 by Genie Industries Patents Pending, 08/02 Part No. B72521EU