


Specifications

| MODELS | DPL™-25S | | DPL™-30S | | DPL™-35S | |
|-----------------|-------------|--------|-------------|---------|-------------|---------|
| | US | Metric | US | Metric | US | Metric |
| Working height* | 31 ft 4 in | 9.70 m | 36 ft | 11.14 m | 40 ft 10 in | 12.62 m |
| Platform height | 25 ft 4 in | 7.70 m | 30 ft | 9.14 m | 34 ft 10 in | 10.62 m |
| Height - stowed | 6 ft 6 in | 1.98 m | 6 ft 6 in | 1.98 m | 6 ft 6 in | 1.98 m |
| Length - stowed | 6 ft 10 in | 2.08 m | 6 ft 10 in | 2.08 m | 6 ft 10 in | 2.08 m |
| Width | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m |



PRODUCTIVITY

| | | | | | | |
|--------------------------------|---------|--------|---------|--------|---------|--------|
| Lift capacity: ANSI (Domestic) | 750 lbs | 340 kg | 750 lbs | 340 kg | 600 lbs | 272 kg |
| CE (European) | 750 lbs | 340 kg | 750 lbs | 340 kg | 600 lbs | 272 kg |
| CSA (Canadian) | 600 lbs | 272 kg | 600 lbs | 272 kg | 500 lbs | 227 kg |

| ANSI | | | | | | |
|----------------------|-------------|--------|------------|--------|------------|--------|
| Outrigger footprint: | | | | | | |
| A length | 6 ft 10 in | 2.08 m | 7 ft 2 in | 2.18 m | 7 ft 2 in | 2.18 m |
| B width | 4 ft 8.5 in | 1.44 m | 5 ft 8 in | 1.73 m | 5 ft 8 in | 1.73 m |
| C corner access | 1 ft 5 in | .43 m | 2 ft | .61 m | 2 ft | .61 m |
| D wall access front | 7 in | .18 m | 9 in | .23 m | 9 in | .23 m |
| E wall access side | 1 ft 4 in | .41 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m |

| CSA | | | | | | |
|----------------------|--------------|--------|------------|--------|------------|--------|
| Outrigger footprint: | | | | | | |
| A length | 7 ft 5 in | 2.26 m | 7 ft 2 in | 2.18 m | 7 ft 9 in | 2.36 m |
| B width | 6 ft 4.25 in | 1.94 m | 5 ft 8 in | 1.73 m | 7 ft 2 in | 2.18 m |
| C corner access | 2 ft 5 in | .74 m | 2 ft 10 in | .86 m | 2 ft 10 in | .86 m |
| D wall access front | 11 in | .28 m | 1 ft 1 in | .33 m | 1 ft 1 in | .33 m |
| E wall access side | 2 ft 3 in | .69 m | 2 ft 7 in | .79 m | 2 ft 7 in | .79 m |

| CE | | | | | | |
|----------------------|-------------|--------|--------------|--------|--------------|--------|
| Outrigger footprint: | | | | | | |
| A length | 6 ft 10 in | 2.08 m | 7 ft 2.25 in | 2.19 m | 7 ft 2.25 in | 2.19 m |
| B width | 4 ft 8.5 in | 1.44 m | 5 ft 8.75 in | 1.75 m | 5 ft 8.75 in | 1.75 m |
| C corner access | 1 ft 5 in | .43 m | 2 ft | .61 m | 2 ft | .61 m |
| D wall access front | 7 in | .18 m | 9 in | .23 m | 9 in | .23 m |
| E wall access side | 1 ft 4 in | .41 m | 1 ft 10 in | .56 m | 1 ft 10 in | .56 m |

| | | | | | | |
|-----------------|-------------|--------|-------------|--------|-------------|--------|
| Platform length | 6 ft | 1.83 m | 6 ft | 1.83 m | 6 ft | 1.83 m |
| Platform width | 2 ft 3.5 in | .70 m | 2 ft 3.5 in | .70 m | 2 ft 3.5 in | .70 m |

POWER

| | |
|-------------------------|--------------------------------------|
| Power source: AC models | 110 V / 50-60 Hz or 220 V / 50-60 Hz |
| DC models | 12 V |

WEIGHT**

| | | | | | | |
|-----------|-----------|--------|-----------|--------|-----------|--------|
| ANSI (AC) | 1,371 lbs | 622 kg | 1,474 lbs | 669 kg | 1,574 lbs | 714 kg |
| ANSI (DC) | 1,481 lbs | 672 kg | 1,584 lbs | 718 kg | 1,684 lbs | 764 kg |
| CE (AC) | 1,371 lbs | 622 kg | 1,474 lbs | 669 kg | 1,645 lbs | 746 kg |
| CE (DC) | 1,481 lbs | 672 kg | 1,584 lbs | 718 kg | 1,755 lbs | 796 kg |
| CSA (AC) | 1,383 lbs | 627 kg | 1,479 lbs | 671 kg | 1,745 lbs | 792 kg |
| CSA (DC) | 1,493 lbs | 677 kg | 1,589 lbs | 721 kg | 1,789 lbs | 811 kg |

STANDARDS COMPLIANCE

ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Weight will vary depending on options and/or country standards

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- 6 ft x 2 x 3.5 in (1.83 m x .70 m)

POWER OPTIONS

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V / 190 amp battery

STANDARD FEATURES

MEASUREMENTS

DPL™-25S

- 31 ft 4 in (9.55 m) working height
- 25 ft 4 in (7.72 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

DPL™-30S

- 36 ft (10.97 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

DPL™-35S

- 40 ft 10 in (12.62 m) working height
- 34 ft 10 in (10.62 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 500-600 lb (227-272 kg) lift capacity

PRODUCTIVITY

- Large platform with room for 1-2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights confirm proper set-up of outriggers
- Winch attachment points
- Locking key switch

POWER

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Operational working light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

Effective Date: July, 2007. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex® is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie® is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. Copyright © 2007 Terex Corporation.