

Specifications

MODEL		GS™-3384 RT	
MEASUREMENTS		US	Metric
Working height maximum*		39 ft	12.06 m
A	Platform height maximum	33 ft	10.06 m
B	Platform length:	12 ft 8 in	3.89 m
	outside, extended - single deck	17 ft 6.25 in	5.34 m
	outside, extended - dual deck	21 ft 6.5 in	6.57 m
C	Slide-out platform extension deck - front	5 ft	1.52 m
D	Slide-out platform extension deck - rear	4 ft	1.22 m
E	Platform width - outside	6 ft	1.83 m
Platform height - stowed**		5 ft 1 in	1.55 m
F	Height - stowed:		
	folding guardrails	8 ft 9.5 in	2.68 m
	rails lowered	6 ft 6.75 in	2.0 m
G	Length - stowed:		
	single deck	12 ft 11.25 in	3.94 m
	dual deck	13 ft 5 in	3.98 m
	with outriggers	16 ft	4.88 m
H	Width:		
	standard tires	7 ft	2.13 m
	high flotation tires	7 ft 11 in	2.41 m
I	Wheelbase	9 ft 4 in	2.84 m
J	Ground clearance - center	13 in	.33 m


PRODUCTIVITY		
Lift capacity	2,500 lbs	1,134 kg
Lift capacity - extension deck	500 lbs	227 kg
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised	0.7 mph	1.1 km/h
Gradeability - stowed***	50%	
Maximum outrigger leveling:	front to back	7°
	side to side	12°
Turning radius - inside	10 ft 1.5 in	3.09 m
Turning radius - outside	19 ft 6 in	5.94 m
Raise/lower speed	45/29 sec	
Controls	proportional	
Drive	four wheel	
Tires - foam-filled rough terrain	10 x 31 in	25 x 79 cm

POWER	
Power source	Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW) Deutz F3L-1011 3 cylinder diesel 49 hp (36 kW) air cooled
Auxiliary Power unit	12 V DC
Fuel tank capacity	30 gal 113.6 L
Hydraulic system capacity	30 gal 113.6 L

WEIGHT****	
	12,005 lbs 5,445 kg

STANDARDS COMPLIANCE ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10, PB-10-611-03

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.



Features

STANDARD FEATURES

MEASUREMENTS

- 39 ft (12.06 m) working height
- Up to 2,500 lb (1,134 kg) lift capacity

PRODUCTIVITY

- 155.25 x 72 in (3.94 x 1.83 m) steel platform
- 60 in (1.52 m) extension deck
- Diamond plate deck
- Folding guardrails
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Full height swing gate
- Two self-closing gates
- 4WD
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

POWER

- 12 V DC auxiliary power

OPTIONS & ACCESSORIES

PRODUCTIVITY

- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Automatic leveling hydraulic outriggers
- Air line to platform
- Pipe cradle (pair)
- High flotation air-filled tires 16 x 33 in (41 x 84 cm)
- High flotation foam-filled tires 16 x 33 in (41 x 84 cm)
- Non-marking rough terrain tires 10 x 31 in (25 x 79 cm)
- Dual flashing beacons
- Motion alarm
- Platform work lights

POWER OPTIONS

- Ford gas/LPG 75 hp (56kW)
- Deutz diesel 49 hp (36 kW)
- 2000 watt generator (110V/60Hz)
- Cold start packages for all engines
- Hydraulic oil cooler
- Diesel scrubber/spark arrestor
- Diesel spark arrestor (without scrubber)
- LPG steel tank only, 33.5 lb capacity
- Additional LPG tank and carrier



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

For further information, please contact your local distributor or the Genie Industries sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2006 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a Terex Company.