


# Specifications



MODELS	SLA™-5		SLA™-10		SLA™-15		SLA™-20		SLA™-25	
	US	Metric	US	Metric	US	Metric	US	Metric	US	Metric
<b>Working height:</b>										
standard forks - up	6 ft 7 in	2.0 m	11 ft 5.5 in	3.49 m	16 ft 4 in	4.98 m	21 ft 2.5 in	6.46 m	26 ft .5 in	7.94 m
standard forks - down	4 ft 10.5 in	1.49 m	9 ft 9 in	2.97 m	14 ft 7.5 in	4.46 m	19 ft 6 in	5.94 m	24 ft 4 in	7.42 m
adjustable forks - up	6 ft 7 in	2.0 m	11 ft 5.5 in	3.49 m	16 ft 4 in	4.98 m	21 ft 2.5 in	6.46 m	26 ft .5 in	7.94 m
adjustable forks - down	4 ft 10.5 in	1.49 m	9 ft 9 in	2.97 m	14 ft 7.5 in	4.46 m	19 ft 6 in	5.94 m	24 ft 4 in	7.42 m
flat forks	4 ft 10.5 in	1.49 m	9 ft 9 in	2.97 m	14 ft 7.5 in	4.46 m				
boom***	5 ft 10.5 in	1.79 m	10 ft 9 in	3.28 m	15 ft 7.5 in	4.76 m	20 ft 6 in	6.25 m	24 ft 4 in	7.42 m
load platform** - forks up	6 ft 7 in	2.0 m	11 ft 5.5 in	3.49 m	16 ft 4 in	4.98 m	21 ft 2.5 in	6.46 m	26 ft .5 in	7.94 m
load platform** - forks down	4 ft 10.5 in	1.49 m	9 ft 9 in	2.97 m	14 ft 7.5 in	4.46 m	19 ft 6 in	5.94 m	24 ft 4 in	7.42 m
<b>A</b> Height - stowed	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m
<b>B</b> Length - stowed	2 ft 5 in	.74 m	2 ft 5 in	.74 m	2 ft 5 in	.74 m	2 ft 5 in	.74 m	2 ft 7 in	.79 m
<b>C</b> Length - operating	4 ft 11.5 in	1.51 m	4 ft 11.5 in	1.51 m	6 ft 2 in	1.88 m	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m
<b>D</b> Width - stowed*	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m
- with stabilizers lowered	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m
<b>Width - straddle base*</b>										
minimum	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	_____	_____	_____	_____
maximum	4 ft 10 in	1.47 m	4 ft 10 in	1.47 m	4 ft 10 in	1.47 m	_____	_____	_____	_____
maximum inside	4 ft 2 in	1.27 m	4 ft 2 in	1.27 m	4 ft 2 in	1.27 m	_____	_____	_____	_____
<b>E</b> Ground clearance - center	2 in	.05 m	2 in	.05 m	2 in	.05 m	2 in	.05 m	2 in	.05 m
<b>F</b> Load height minimum	6 in	.15 m	6 in	.15 m	6 in	.15 m	6 in	.15 m	6 in	.15 m

## PRODUCTIVITY

<b>Load capacity:</b>										
18 in (46 cm) load center	1,000 lbs	454 kg	1,000 lbs	454 kg	800 lbs	363 kg	800 lbs	363 kg	650 lbs	295 kg
24 in (61 cm) load center	1,000 lbs	454 kg	1,000 lbs	454 kg	800 lbs	363 kg	600 lbs	272 kg	450 lbs	204 kg
42 in (1.07 m) load center	350 lbs	159 kg	400 lbs	181 kg	500 lbs	227 kg	350 lbs	159 kg	250 lbs	113 kg

## POWER

Power source	One speed or two speed winch
--------------	------------------------------

## WEIGHT

Standard	215 lbs	98 kg	260 lbs	118 kg	333 lbs	151 kg	405 lbs	184 kg	450 lbs	204 kg
Straddle base	258 lbs	117 kg	303 lbs	137 kg	360 lbs	163 kg	_____	_____	_____	_____

## LOAD HANDLING ATTACHMENTS

MEASUREMENTS	US	Metric	Weight - US	Weight - Metric
Standard forks (l/w/d)****	27.5/23.5/2.5 in	70/60/6 cm	38.9 lbs	18 kg
Adjustable forks (l/w/d)****	27.5/11.5-30/2.5 in	70/29-76/6 cm	52.5 lbs	24 kg
Fork extensions detached (each) (l/w/d)****	30/2/3 in	76/5/8 cm	4.5 lbs	2 kg
Fork extensions attached (each) (l/w/d)****	25/2/3 in	64/5/8 cm	4.5 lbs	2 kg
Flat forks (l/w/d)****	32/16-31/1.5 in	81/41-79/3.8 cm	80.1 lbs	36 kg
Boom (l/w/d)****	18-42/1.5/6.5 in	46-107/4/16.5 cm	39.9 lbs	18 kg
Pipe cradle (l/w/d)****/*****	27.5/24.5/6 in	70/62/15.2 cm	10 lbs	4.5 kg
Load platform (l/w/d)****	27.5/23.5/2.5 in	70/60/6 cm	31.5 lbs	14 kg

\* Outside dimensions.  
 \*\* For use with standard and adjustable forks only.  
 \*\*\* Measured from ground to bottom of shackle.  
 \*\*\*\* Length/width/depth.  
 \*\*\*\*\* Handles round objects up to 30 in (76 cm) in diameter.  
 SLA5 3K 0107F. Part No. 109381

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### FORK OPTIONS

- Standard forks
- Adjustable forks
- Fork extensions
- Flat forks (SLA™-5, -10, -15 only)
- Boom
- Pipe cradle
- Load platform

#### POWER OPTIONS

- One-speed winch
- Two-speed winch

#### BASE OPTIONS

- Standard base
- Straddle base (SLA™-5, -10, -15 only)
- Stabilizer set (standard on SLA™-20, -25, not available on straddle base)

#### CASTER & BRAKE OPTIONS

- 4 in (10 cm) front casters with side brakes
- 5 in (13 cm) rear casters with side brakes
- Fixed front caster option
- Rear transport wheel assembly

### STANDARD FEATURES

#### MEASUREMENTS

##### SLA™-5

- 6 ft 7 in (2.0 m) working height
- Up to 1,000 lb (454 kg) load capacity

##### SLA™-10

- 11 ft 5.5 in (3.49 m) working height
- Up to 1,000 lb (454 kg) load capacity

##### SLA™-15

- 16 ft 4 in (4.98 m) working height
- Up to 800 lb (363 kg) load capacity

##### SLA™-20

- 21 ft 2.5 in (6.46 m) working height
- Up to 800 lb (363 kg) load capacity

##### SLA™-25

- 26 ft .5 in (7.94 m) working height
- Up to 650 lb (295 kg) load capacity

#### PRODUCTIVITY

- Heavy-duty design
- Patented telescoping mast system
- Captive stabilizer set (standard on SLA™-20, -25)
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Maneuverable 4 in (10 cm) front casters and 5 in (13 cm) rear casters, with 4-way swivel locks and side brakes, are standard
- Compact design, legs fold up for easy storage
- Roller wheels allow easy transport in stowed position
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport

#### POWER

- One speed winch



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Standard forks
- Adjustable forks
- Fork extensions
- Flat forks
- Boom
- Pipe cradle
- Load platform
- Fixed front caster
- Captive stabilizer set (option on SLA™-5, -10, 15)
- Rear transport wheel assembly

#### POWER

- Two speed winch

### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**  
Toll Free in USA/Canada **800-536-1800**  
Fax (425) 883-3475

### Genie Europe

The Maltings  
Wharf Road  
Grantham NG31 6BH  
U.K.

Telephone **+44 (0)1476 584333**  
Fax +44 (0)1476 584334

Email: [infoeurope@genieind.com](mailto:infoeurope@genieind.com)

### Distributed By:

For further information, please contact your local distributor or the Genie Industries sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2006 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a Terex Company.