MANITRANSIT - TMT 2017 C





TMT 2017 C

ì		
I	$ egthinspace{-1mm}$	П
l	\sim	
		,

CAPACITY

Maximum capacity2000 kg



LIFTING

Maximum lifting height	.2870	mm
Maximum front reach	.1120	mm
Side-shift	150	mm



ENGINE / TRANSMISSION

Туре	.KUBOTA	(27	HP)
Hydrostatic transmission			
Driving wheels			3



TYRES

Front tyres18X	7,8	16PR
Rear tyre18X	7,8	16PR



DIMENSIONS

Width22	03 mm
Height20	72 mm
Overhang (in transport position)11	70 mm
Weight (without equipment)1	816 kg

IN STANDARD

ROPS/FOPS Cab + load indicator FNR joystick Waterproof dashboard and electric connections Differential lock Cataphoresis point

OPTIONS

Full mounting kit Load repartition calculation (on request) Rearview mirrors Rotating beacon Road lights Working lights and reversing light Load backrest

NEW FNR JOYSTICK



This new « boom control » joystick now integrates the « reversing shift » function : the driver can keep one hand on the steering wheel and one hand on this joystick to operate any movement. Time saving and much better driving position.



This publication in no way constitutes an offer and the company reserves the right to alter specification without prior notice. The MANITOU models presented in this brochure can be supplied complete with optional equipment attachments. IMPORTANT: All regulations relating to vehicles apply to vehicles equipped with truck-mounted forklifts.

50° 40° 40° 40° 2.87 20° 10° 20° -30° -30° -30° -50° -50°

BOOM



Enables you to offload your lorry with the best visibility ever.

COMPACT



With its new design, the MANITRANSIT is more ergonomic : spacefull cab, full 360° visibility...



B.P. 249 - 44158 Ancenis Cedex - France Tél.: 33 2 40 09 10 11 / Export Department Fax: 33 2 40 09 10 97 www.manitou.com

700304EN - Doc. BE 312/Ind. B

