MANITRANSIT - TMT 2020 S



TMT 2020 S

\sim	
	•

CAPACITY

Maximum Capacity......2000 kg



LIFTING

Maximum lifting height	.2980 mm
Maximum front reach	.1030 mm
Side-shift	150 mm



ENGINE / TRANSMISSION

Type	.KUBOTA	(27	HP)
Hydrostatic transmission			
Driving wheels			3



TYRES

Front tyres	26x12-12	10	PR
Rear tyre	26x12-12	10	PR



DIMENSIONS

Width	.2449	mm
Height	.2159	mm
Overhang (in transport position)	.1170	mm
Weight (without equipment)	191	1 kg

IN STANDARD

ROPS/FOPS Cab + load indicator FNR joystick Waterproof dashboard and electric connections Stabilisers Differential lock

OPTIONS

Full mounting kit
Load repartition calculation (on request)
Rearview mirrors
Rotating beacon
Road lights
Working lights and reversing light
Load backrest

NEW FNR JOYSTICK



This new « boom control » joystick now integrates the « reversing shift » function : the driver can keep one hand on the steering wheel and one hand on this joystick to operate any movement. Time saving and much better driving position.



This publication in no way constitutes an offer and the company reserves the right to alter specification without prior notice. The MANITOU models presented in this brochure can be supplied complete with optional equipment attachments. IMPORTANT: All regulations relating to vehicles apply to vehicles equipped with truck-mounted forkling.

ВООМ



Enables you to offload your lorry with the best visibility ever.

STABILISERS



The 2 front stabilisers of the TMT 2020 S give more lifting capacity, especially when the boom is fully extended at maximum reach.

