


SKYTOWER

SVO6CNU AICHI GLOBAL SERIES SVO8CNU SCISSORS MODEL



SKYTOWER SV06CNL & SV08CNL provide high performance with proportional steering system at working sites.

SV06CNL & SV08CNL achieved long duty cycle with AC motor drive.

LONG DUTY CYCLE

AC DRIVING MOTOR improved a duty cycle150% more as compared with our previous model.

In addition the Non-brush motor will contribute to reduce the running costs.

OPERATION SYSTEM

Proportional Drive Control System offers smooth operation. (Option)



90 degrees Steering angle (Front wheel) provides a small turning radius.



COMPACT BODY & LARGE PLATFORM

Compact Stowed position with Fold Down Handrail


Platform 2.21m in length plus Extension deck (1.0m)



1,720mm (SV06CNL) 1,845mm (SV08CNL) Extension deck 1,000mm

CAUTION) LL PHOTOS:SV08CNL PTION DEVICES EQUIPPED, TANDARD PAINTING COLOR





■WIDE RANGE OF CHARGING VOLTAGE AC100-240V can apply for.



■SLIDE-OUT TRAY


Battery maintenance can be apphed by slide-out tray.





■ EASY ACCESS TO EQUIPMENTS


Parts can be removed or adjusted with the wrench of 0.4in(10mm) and 0.5in(13mm), phillips-head screwdriver.

DIMENSIONS











AICHI CORPORATION

Overseas Sales & Marketing Department http://www.aichi-corp.jp

DISTRIBUTORS

MAJOR SPECIFICATIONS

For European Market

● MODEL		
Model	SV06CNL	SV08CNL
● PLATFORM		
Platform Capacity	360kg	230kg
Platform Extension	1.0m	
Platform Hight-elevated	6.1m	7.77m
Platform Hight-Lowered	1.025m	1.115m
Platform Size	$2.21m\times0.71m\times1.1m$	
●LIFT & LOWER SYSTEM		
Туре	3 scissors link	4 scissors link
Lifting / Lowering time	30sec	40sec
●POWER SYSTEM		
Batteries	24V	
Tyre Type	Solid	
•TRAVEL DEVICE		
Speed	Max 4.5km/stowed, 1.0km/lifted	
Gradeability	14degree	
● DIMENSION		
A Overall Width	0.8m	
B Overall Height	2.125m	2.255m
C Overall Length	2.3m	
D Ground Clearance	0.115m/stowed, 0.015m/pot hole	
Vehicle Weight	1,810kg	2,140kg
OPTIONAL EQUIPMENTS		
Proportional steering		

The AICHI "2 - 3 - 5 " Warranty

AICHI CORPORATION backs its products with its exclusive " 2 - 3 - 5 " Warranty.

two (2) years; Basic warranty parts three (3) years.:Specified Hydraulic components

five (5) years.; Structual components

Note; Due to continuous products improvements, we reserve the right to make specification and / or equipment changes without prior notification.